

## Hot Air Gun HG 2310 LCD

Powerful, electronically controlled professional hot air gun with continuously adjustable airflow and temperature control; as well as LCD display.

- Sturdy housing for hand-held and self-resting use
- Continuously adjustable temperature
- Continuously adjustable speed
- LCD showing temperature and RPM's
- Four preset programmes
- Capability of changing the four preset programmes as required
- Double overheating protection: thermostat and thermal cut-out
- Air intake mesh filter to prevent debris entering unit
- Soft grip handle and soft stand for stability



COLD/ON/OFF



Soft grip handle



Hand-held



Self-resting



Accessories



HG 2310 LCD



- Visual display of temperature and RPM's on LCD
- Programming button for 4 preset programmes
- Set button for changing preset programmes
- Continuously adjustable temperature
- Continuously adjustable airflow
- Non-slip end cap

### HG 2310 LCD

|              |   |
|--------------|---|
| Dimensions:  | 260 x 90 x 205 mm   |
| Voltage:     | 230 V / 50 Hz   |
| Output:      | 2300 W  |
| Display:     | LCD in 10 °C - steps  |
| Air flow:    | continuously adjustable   |
| Air volume:  | Stage 1: 150 – 250 l/min.<br>Stage 2: 150 – 500 l/min.  |
| Programms:   | Factory setting<br>1 = 250 °C / ca. 350 l/min.<br>2 = 350 °C / ca. 400 l/min.<br>3 = 450 °C / ca. 500 l/min.<br>4 = 550 °C / ca. 400 l/min. |
| Set button:  | for changing preset programmes  |
| Temperature: | Stage 1: 50° C<br>Stage 2: 50 – 650° C  |
| Weight:      | 940 g   |